

# T5 and T8 Fluorescent Lamps

Linear and U-Bent



LIGHTING PRODUCTS


## Applications



- Offices
- Hallways
- Stairwells
- Warehouses
- Hospitals
- Classrooms

**HOWARD**<sup>TM</sup>  
LIGHTING PRODUCTS

Lighting **for life.**



**HOWARD**<sup>TM</sup>  
LIGHTING PRODUCTS  
F17T8/835/ECO  
17 WATT, 3500 K, 85 CRI  
MADE IN GERMANY CCC

Visit us online at [HowardLightingProducts.com](http://HowardLightingProducts.com) or call us at 800.956.3456.

# Howard's best-in-class T5 and T8 lamps.

T5 and T8 fluorescent lighting is quickly becoming the lamp of choice in both residential and commercial applications due to their many features and configurations. With a wide selection of wattages, sizes, and designs, our T5 and T8 fluorescent lamp options provide energy savings and reduced maintenance costs while providing you with high color rendition and consistent quality light output. Howard Lighting continually strives to provide you with superior lighting products where you need them most...Life.



T5



T8



Lighting **for life**™

Visit us online at [HowardLightingProducts.com](http://HowardLightingProducts.com) or call us at 800.956.3456.

Experience the  
**Howard advantage.**

**HOWARD**<sup>TM</sup>  
LIGHTING PRODUCTS

**HI** A Division of Howard Industries, Inc.



U-BENT T8

*We make ordering as easy as 1-2-3.*

**1.** **Order Direct**  
Contact the authorized agent that you have purchased from in the past.

**2.** **Order by phone**  
You can also contact us at 800.956.3456 to discuss your needs or place an order.

**3.** **Order by fax**  
Or if you prefer, you can reach us by fax at 601.422.1652.

# Product Offerings


Watts	Bulb	Nominal Length (in)	MOL (in)	Base	UPC #	Howard Catalog #	Lumens Initial (lm) @ 35° C	Lumens Mean (lm) @ 35° C	Avg. Life (hours)	Color Temp. (K)	CRI	Pkg. Qty.	Footnotes
<b>T5 Fluorescent</b>													
14	T5	24	22.2	Mini Bipin (G5)	799385-01541	F14T5/830	1350	1269	20000	3000	85	25	1,2,3,4,5,6,7
14	T5	24	22.2	Mini Bipin (G5)	799385-01542	F14T5/835	1350	1269	20000	3500	85	25	1,2,3,4,5,6,7
14	T5	24	22.2	Mini Bipin (G5)	799385-01543	F14T5/841	1350	1269	20000	4100	85	25	1,2,3,4,5,6,7
14	T5	24	22.2	Mini Bipin (G5)	799385-01544	F14T5/865	1350	1269	20000	6500	85	25	1,2,3,4,5,6,7
21	T5	36	34	Mini Bipin (G5)	799385-01545	F21T5/830	2100	1974	20000	3000	85	25	1,2,3,4,5,6,7
21	T5	36	34	Mini Bipin (G5)	799385-01546	F21T5/835	2100	1974	20000	3500	85	25	1,2,3,4,5,6,7
21	T5	36	34	Mini Bipin (G5)	799385-01547	F21T5/841	2100	1974	20000	4100	85	25	1,2,3,4,5,6,7
21	T5	36	34	Mini Bipin (G5)	799385-01548	F21T5/865	2100	1974	20000	6500	85	25	1,2,3,4,5,6,7
28	T5	48	45.8	Mini Bipin (G5)	799385-01549	F28T5/830	2900	2726	20000	3000	85	25	1,2,3,4,5,6,7
28	T5	48	45.8	Mini Bipin (G5)	799385-01550	F28T5/835	2900	2726	20000	3500	85	25	1,2,3,4,5,6,7
28	T5	48	45.8	Mini Bipin (G5)	799385-01551	F28T5/841	2900	2726	20000	4100	85	25	1,2,3,4,5,6,7
28	T5	48	45.8	Mini Bipin (G5)	799385-01552	F28T5/865	2900	2726	20000	6500	85	25	1,2,3,4,5,6,7
35	T5	60	57.6	Mini Bipin (G5)	799385-01553	F35T5/830	3650	1974	20000	6500	85	25	1,2,3,4,5,6,7
35	T5	60	57.6	Mini Bipin (G5)	799385-01554	F35T5/835	2100	1974	20000	6500	85	25	1,2,3,4,5,6,7
35	T5	60	57.6	Mini Bipin (G5)	799385-01555	F35T5/841	2100	1974	20000	6500	85	25	1,2,3,4,5,6,7
35	T5	60	57.6	Mini Bipin (G5)	799385-01556	F35T5/865	2100	1974	20000	6500	85	25	1,2,3,4,5,6,7
<b>T5 HO Fluorescent</b>													
24	T5	24	22.2	Mini Bipin (G5)	799385-01557	F24T5/830/HO	2000	1880	20000	3000	85	25	1,2,3,4,5,6,7
24	T5	24	22.2	Mini Bipin (G5)	799385-01558	F24T5/835/HO	2000	1880	20000	3500	85	25	1,2,3,4,5,6
24	T5	24	22.2	Mini Bipin (G5)	799385-01559	F24T5/841/HO	2000	1880	20000	4100	85	25	1,2,3,4,5,6
24	T5	24	22.2	Mini Bipin (G5)	799385-01560	F24T5/865/HO	2000	1880	20000	6500	85	25	1,2,3,4,5,6,7
39	T5	36	34	Mini Bipin (G5)	799385-01561	F39T5/830/HO	3500	3290	20000	3000	85	25	1,2,3,4,5,6,7
39	T5	36	34	Mini Bipin (G5)	799385-01562	F39T5/835/HO	3500	3290	20000	3500	85	25	1,2,3,4,5,6
39	T5	36	34	Mini Bipin (G5)	799385-01563	F39T5/841/HO	3500	3290	20000	4100	85	25	1,2,3,4,5,6
39	T5	36	34	Mini Bipin (G5)	799385-01564	F39T5/865/HO	3500	3290	20000	6500	85	25	1,2,3,4,5,6,7
54	T5	48	45.8	Mini Bipin (G5)	799385-01569	F54T5/830/HO	5000	4700	20000	3000	85	25	1,2,3,4,5,6
54	T5	48	45.8	Mini Bipin (G5)	799385-01570	F54T5/835/HO	5000	4700	20000	3500	85	25	1,2,3,4,5,6
54	T5	48	45.8	Mini Bipin (G5)	799385-01571	F54T5/841/HO	5000	4700	20000	4100	85	25	1,2,3,4,5,6,7
54	T5	48	45.8	Mini Bipin (G5)	799385-01572	F54T5/865/HO	5000	4700	20000	6500	85	25	1,2,3,4,5,6,7
80	T5	60	57.6	Mini Bipin (G5)	799385-01573	F80T5/830/HO	7000	6580	20000	3000	85	25	1,2,3,4,5,6,7
80	T5	60	57.6	Mini Bipin (G5)	799385-01574	F80T5/835/HO	7000	6580	20000	3500	85	25	1,2,3,4,5,6,7
80	T5	60	57.6	Mini Bipin (G5)	799385-01575	F80T5/841/HO	7000	6580	20000	4100	85	25	1,2,3,4,5,6,7
80	T5	60	57.6	Mini Bipin (G5)	799385-01576	F80T5/865/HO	7000	6580	20000	6500	85	25	1,2,3,4,5,6,7

**Footnote Legend:**

- 1 Average-rated life is based on 3 hours per start.
- 2 Average-rated life at 12 hours per start will increase life by approximately 25% (e.g., lamps rated at 20000 would go to 25000).
- 3 Lumen ratings, CRI and average-rated lamp life subject to change.
- 4 NEMA recommends that ballasts for this lamp have end-of-life shutdown circuitry which will safely shut the system down in the event of an abnormal end-of-life failure mode. See [www.NEMA.org](http://www.NEMA.org) for details.
- 5 Minimum start temperature is a function of the ballast; consult the ballast manufacturer.
- 6 The nominal length of linear fluorescent lamps is typically measured from back of lampholder to back of lampholder. T5 and T5HO linear lamps are exceptions. The nominal length given for T5 and T5HO linear lamps is the closest familiar nominal length.
- 7 Call for availability.

**HOWARD**<sup>™</sup>  
LIGHTING PRODUCTS

Lighting for life.



Visit us online at [HowardLightingProducts.com](http://HowardLightingProducts.com) or call us at 800.956.3456.

# Product Offerings

Watts	Bulb	Nominal Length (in)	MOL (in)	Base	UPC #	Howard Catalog #	Lumens Initial (lm)	Lumens Mean (lm)	Avg. Life (hours)	Color Temp. (K)	CRI	Pkg. Qty.	Footnotes
<b>T8 Fluorescent Low Mercury</b>													
17	T8	24	23.78	Med Bipin	799385-01502	F17T8/730/ECO	1325	1260	24000	3000	75	25	1,2,3,ECO
17	T8	24	23.78	Med Bipin	799385-01503	F17T8/735/ECO	1325	1260	24000	3500	75	25	1,2,3,ECO
17	T8	24	23.78	Med Bipin	799385-01504	F17T8/741/ECO	1325	1260	24000	4100	75	25	1,2,3,ECO
17	T8	24	23.78	Med Bipin	799385-01505	F17T8/830/ECO	1350	1280	24000	3000	85	25	1,2,3,ECO
17	T8	24	23.78	Med Bipin	799385-01506	F17T8/835/ECO	1350	1280	24000	3500	85	25	1,2,3,ECO
17	T8	24	23.78	Med Bipin	799385-01507	F17T8/841/ECO	1350	1280	24000	4100	85	25	1,2,3,ECO
25	T8	36	35.78	Med Bipin	799385-01508	F25T8/730/ECO	2080	1970	24000	3000	75	25	1,2,3,ECO
25	T8	36	35.78	Med Bipin	799385-01509	F25T8/735/ECO	2080	1970	24000	3500	75	25	1,2,3,ECO
25	T8	36	35.78	Med Bipin	799385-01510	F25T8/741/ECO	2080	1970	24000	4100	75	25	1,2,3,ECO
25	T8	36	35.78	Med Bipin	799385-01511	F25T8/830/ECO	2150	2040	24000	3000	85	25	1,2,3,ECO
25	T8	36	35.78	Med Bipin	799385-01512	F25T8/835/ECO	2150	2040	24000	3500	85	25	1,2,3,ECO
25	T8	36	35.78	Med Bipin	799385-01513	F25T8/841/ECO	2150	2040	24000	4100	85	25	1,2,3,ECO
28	T8	48	47.78	Med Bipin	799385-01514	F28T8/830/ES/ECO	2725	2560	24000	3000	85	25	1,2,3,ⓔ,ECO
28	T8	48	47.78	Med Bipin	799385-01515	F28T8/835/ES/ECO	2725	2560	24000	3500	85	25	1,2,3,ⓔ,ECO
28	T8	48	47.78	Med Bipin	799385-01516	F28T8/841/ES/ECO	2725	2560	24000	4100	85	25	1,2,3,ⓔ,ECO
30	T8	48	47.78	Med Bipin	799385-01517	F30T8/830/ES/ECO	2850	2680	24000	3000	85	25	1,2,3,ⓔ,ECO
30	T8	48	47.78	Med Bipin	799385-01518	F30T8/835/ES/ECO	2850	2680	24000	3500	85	25	1,2,3,ⓔ,ECO
30	T8	48	47.78	Med Bipin	799385-01519	F30T8/841/ES/ECO	2850	2680	24000	4100	85	25	1,2,3,ⓔ,ECO
32	T8	48	47.78	Med Bipin	799385-01520	F32T8/730/ECO	2850	2710	24000	3000	75	25	1,2,3,ⓔ,ECO
32	T8	48	47.78	Med Bipin	799385-01521	F32T8/735/ECO	2850	2710	24000	3500	75	25	1,2,3,ⓔ,ECO
32	T8	48	47.78	Med Bipin	799385-01522	F32T8/741/ECO	2850	2710	24000	4100	75	25	1,2,3,ⓔ,ECO
32	T8	48	47.78	Med Bipin	799385-01523	F32T8/830/ECO	2950	2800	24000	3000	85	25	1,2,3,ⓔ,ECO
32	T8	48	47.78	Med Bipin	799385-01524	F32T8/835/ECO	2950	2800	24000	3500	85	25	1,2,3,ⓔ,ECO
32	T8	48	47.78	Med Bipin	799385-01525	F32T8/841/ECO	2950	2800	24000	4100	85	25	1,2,3,ⓔ,ECO
32	T8	48	47.78	Med Bipin	799385-01947	F32T8/830/HL/ECO	3100	2950	24000	3000	85	25	1,2,3,ⓔ,ECO
32	T8	48	47.78	Med Bipin	799385-01948	F32T8/835/HL/ECO	3100	2950	24000	3500	85	25	1,2,3,ⓔ,ECO
32	T8	48	47.78	Med Bipin	799385-01949	F32T8/841/HL/ECO	3100	2950	24000	4100	85	25	1,2,3,ⓔ,ECO
<b>T8 Fluorescent U-Bent, 6" Spacing, Low Mercury</b>													
28	T8	22.5	22.6	Med Bipin	799385-01532	FB28T8/830/ES/ECO	2600	-	24000	3000	85	20	1,2,3,ⓔ,ECO
28	T8	22.5	22.6	Med Bipin	799385-01533	FB28T8/835/ES/ECO	2600	-	24000	3500	85	20	1,2,3,ⓔ,ECO
28	T8	22.5	22.6	Med Bipin	799385-01534	FB28T8/841/ES/ECO	2600	-	24000	4100	85	20	1,2,3,ⓔ,ECO
32	T8	22.5	22.6	Med Bipin	799385-01535	FB32T8/730/6/ECO	2650	-	24000	3000	75	20	1,2,3,ⓔ,ECO
32	T8	22.5	22.6	Med Bipin	799385-01536	FB32T8/735/6/ECO	2650	-	24000	3500	75	20	1,2,3,ⓔ,ECO
32	T8	22.5	22.6	Med Bipin	799385-01537	FB32T8/741/6/ECO	2650	-	24000	4100	75	20	1,2,3,ⓔ,ECO
32	T8	22.5	22.6	Med Bipin	799385-01538	FB32T8/830/6/ECO	2800	-	24000	3000	85	20	1,2,3,ⓔ,ECO
32	T8	22.5	22.6	Med Bipin	799385-01539	FB32T8/835/6/ECO	2800	-	24000	3500	85	20	1,2,3,ⓔ,ECO
32	T8	22.5	22.6	Med Bipin	799385-01540	FB32T8/841/6/ECO	2800	-	24000	4100	85	20	1,2,3,ⓔ,ECO

**Footnote Legend:**

- 1 Average-rated life is based on 3 hours per start.
- 2 Average-rated life at 12 hours per start will increase life by approximately 25% (e.g., lamps rated at 24000 would go to 30000).
- 3 Lumen ratings, CRI and average-rated lamp life subject to change.
- ⓔ This lamp meets Federal Minimum Efficiency standards.
- ECO Low-Mercury fluorescent lamps pass the Federal TCLP for hazardous waste. Disposal regulations may vary; check local and state regulations.




Lighting for life.™

**HOWARD**  
LIGHTING PRODUCTS

# Cross Reference

Watts	Howard	EIKO	GE	Halco	Hygrade	Philips	SLI	Sylvania	USHIO
<b>T5 Fluorescent</b>									
14	F14T5/830	N/A	F14W/T5/830	N/A	N/A	F14T5/830	F14T5/830	FP14/830	F14T5/830
14	F14T5/835	F14T5/835	F14W/T5/835	F14T5/835	N/A	F14T5/835	F14T5/835	FP14/835	F14T5/835
14	F14T5/841	F14T5/841	F14W/T5/841	F14T5/841	N/A	F14T5/841	F14T5/841	FP14/841	F14T5/841
14	F14T5/865	N/A	F14W/T5/865	N/A	N/A	N/A	N/A	N/A	F14T5/860
21	F21T5/830	N/A	F21W/T5/830	F21T5/830	N/A	F21T5/830	F21T5/830	FP21/830	F21T5/830
21	F21T5/835	F21T5/835	F21W/T5/835	F21T5/835	N/A	F21T5/835	F21T5/835	FP21/835	F21T5/835
21	F21T5/841	F21T5/841	F21W/T5/841	F21T5/841	N/A	F21T5/841	F21T5/841	FP21/841	F21T5/841
21	F21T5/865	N/A	F21W/T5/865	N/A	N/A	N/A	N/A	N/A	F21T5/860
28	F28T5/830	N/A	F28W/T5/830	F28T5/830	N/A	F28T5/830	F28T5/830	FP28/830	F28T5/830
28	F28T5/835	F28T5/835	F28W/T5/835	F28T5/835	N/A	F28T5/835	F28T5/835	FP28/835	F28T5/835
28	F28T5/841	F28T5/841	F28W/T5/841	F28T5/841	N/A	F28T5/841	F28T5/841	FP28/841	F28T5/841
28	F28T5/865	N/A	F28W/T5/865	N/A	N/A	N/A	N/A	N/A	F28T5/860
35	F35T5/830	N/A	F35W/T5/830	N/A	N/A	F35T5/830	N/A	FP35/830	F35T5/830
35	F35T5/835	N/A	F35W/T5/835	F35T5/835	N/A	F35T5/835	N/A	FP35/835	F35T5/835
35	F35T5/841	N/A	F35W/T5/841	F35T5/841	N/A	F35T5/841	N/A	FP35/841	F35T5/841
35	F35T5/865	N/A	F35W/T5/865	N/A	N/A	N/A	N/A	N/A	F35T5/860
<b>T5 HO Fluorescent</b>									
24	F24T5/830/HO	N/A	F24W/T5/830	N/A	N/A	F24T5/830/HO/ALTO	F24T5/830/HO	N/A	FP24/830/HO
24	F24T5/835/HO	F24T5/HO/835	F24W/T5/835	F24T5/835/HO	N/A	F24T5/835/HO	F24T5/835/HO	N/A	FP24/835/HO
24	F24T5/841/HO	F24T5/HO/841	F24W/T5/841	F24T5/841/HO	N/A	F24T5/841/HO	F24T5/841/HO	N/A	FP24/841/HO
24	F24T5/865/HO	N/A	F24W/T5/865	N/A	N/A	N/A	N/A	N/A	N/A
39	F39T5/830/HO	N/A	F39W/T5/830	F39T5/830/HO	N/A	F39T5/830/HO	F39T5/830/HO	FP39/830/HO	F39T5HO/830
39	F39T5/835/HO	F39T5/HO/835	F39W/T5/835	F39T5/835/HO	N/A	F39T5/835/HO	F39T5/835/HO	FP39/835/HO	N/A
39	F39T5/841/HO	F39T5/HO/841	F39W/T5/841	F39T5/841/HO	N/A	F39T5/841/HO	F39T5/841/HO	FP39/841/HO	F39T5HO/841
39	F39T5/865/HO	N/A	F39W/T5/865	N/A	N/A	N/A	N/A	N/A	F39T5HO/860
49	F49T5/830/HO	N/A	F49W/T5/830	N/A	N/A	N/A	N/A	N/A	N/A
49	F49T5/835/HO	N/A	F49W/T5/835	N/A	N/A	N/A	N/A	N/A	N/A
49	F49T5/841/HO	N/A	F49W/T5/841	N/A	N/A	N/A	N/A	N/A	N/A
49	F49T5/865/HO	N/A	F49W/T5/865	N/A	N/A	N/A	N/A	N/A	N/A
54	F54T5/830/HO	N/A	F54W/T5/830	F54T5/830/HO	N/A	F54T5/830/HO/ALTO	F54T5/830/HO	FP54/830/HO/ECO	F54T5HO/830
54	F54T5/835/HO	F54T5/HO/835	F54W/T5/835	F54T5/835/HO	N/A	F54T5/835/HO/ALTO	F54T5/835/HO	FP54/835/HO/ECO	N/A
54	F54T5/841/HO	F54T5/HO/841	F54W/T5/841	N/A	N/A	F54T5/841/HO/ALTO	F54T5/841/HO	FP54/841/HO/ECO	F54T5HO/841
54	F54T5/865/HO	N/A	F54W/T5/865	N/A	N/A	N/A	N/A	FP54/860/HO/ECO	F54T5HO/860
80	F80T5/830/HO	N/A	F80W/T5/830	N/A	N/A	F80T5/830/HO	N/A	FP80/830/HO/ECO	N/A
80	F80T5/835/HO	N/A	F80W/T5/835	N/A	N/A	N/A	N/A	PF80/835/HO/ECO	N/A
80	F80T5/841/HO	N/A	F80W/T5/841	N/A	N/A	F80T5/841/HO	N/A	FP80/841/HO/ECO	N/A
80	F80T5/865/HO	N/A	F80W/T5/865	N/A	N/A	N/A	N/A	N/A	N/A



# Cross Reference


Watts	Howard	EIKO	GE	Halco	Hygrade	Philips	SLI	Sylvania
<b>T8 Fluorescent Low Mercury</b>								
17	F17T8/730/ECO	F17T8/730K	F17T8/XL/SP30/ECO	F17T8/730/ECO	N/A	F17T8/TL730/ALTO	F17T8/730	FO17/730/XP/ECO
17	F17T8/735/ECO	F17T8/735K	F17T8/XL/SP35/ECO	F17T8/735/ECO	F17T8/735	F17T8/TL735/ALTO	F17T8/735	FO17/735/XP/ECO
17	F17T8/741/ECO	F17T8/741K	F17T8/XL/SP41/ECO	F17T8/741/ECO	F17T8/741	F17T8/TL741/ALTO	F17T8/741	FO17/741/XP/ECO
17	F17T8/830/ECO	F17T8/830K	F17T8/XL/SPX30/ECO	F17T8/830/ECO	N/A	F17T8/TL830/PLUS/ALTO	F17T8/830	FO17/830/XP/ECO
17	F17T8/835/ECO	F17T8/835K	F17T8/XL/SPX35/ECO	F17T8/835/ECO	N/A	F17T8/TL835/PLUS/ALTO	F17T8/835	FO17/835/XPECO
17	F17T8/841/ECO	F17T8/841K	F17T8/XL/SPX41/ECO	F17T8/841/ECO	N/A	F17T8/TL841/PLUS/ALTO	F17T8/841	FO17/841/XP/ECO
25	F25T8/730/ECO	F25T8/730K	F25T8/XL/SP30/ECO	F25T8/730/ECO	N/A	F25T8/TL730/ALTO	F25T8/730	FO25/730/XP/ECO
25	F25T8/735/ECO	F25T8/735K	F25T8/XL/SP35/ECO	F25T8/735/ECO	F25T8/735	F25T8/TL735/ALTO	F25T8/735	FO25/735/XP/ECO
25	F25T8/741/ECO	F25T8/741K	F25T8/XL/SP41/ECO	F25T8/741/ECO	F25T8/741	F25T8/TL741/ALTO	F25T8/741	FO25/741/XP/ECO
25	F25T8/830/ECO	F25T8/830K	F25T8/XL/SPX30/ECO	F25T8/830/ECO	N/A	F25T8/TL830/PLUS/ALTO	F25T8/830	FO25/830/XP/ECO
25	F25T8/835/ECO	F25T8/835K	F25T8/XL/SPX35/ECO	F25T8/835/ECO	N/A	F25T8/TL835/PLUS/ALTO	F25T8/835	FO25/835/XP/ECO
25	F25T8/841/ECO	F25T8/841K	F25T8/XL/SPX41/ECO	F25T8/841/ECO	N/A	F25T8/TL841/PLUS/ALTO	F25T8/841	FO25/841/XP/ECO
28	F28T8/830/ES/ECO	N/A	F28T8SP30U/MX/ECO	N/A	F28T8/830HL	F32T8/ADV830/EW/LL/ALTO 28 Watt	F32T8/ES/830	FO28/830/XP/SS/ECO
28	F28T8/835/ES/ECO	N/A	F28T8SP35U/MX/ECO	F28T8/835/ECO	F28T8/835/HL	F32T8/ADV835/EW/LL/ALTO 28 Watt	F32T8/ES/835	FO28/835/XP/SS/ECO
28	F28T8/841/ES/ECO	N/A	F28T8SP41U/MX/ECO	F28T8/841/ECO	F28T8/841/HL	F32T8/ADV841/EW/LL/ALTO 28 Watt	F32T8/ES/841	FO28/841/XP/SS/ECO
30	F30T8/830/ES/ECO	N/A	F32T8/XL/SP30/WM/ECO	N/A	N/A	F32T8/ADV830/EW/LL/ALTO 30 Watt	N/A	FO30/830/XP/SS/ECO
30	F30T8/835/ES/ECO	N/A	F32T8/XL/SP35/WM/ECO	N/A	N/A	F32T8/ADV835/EW/LL/ALTO 30 Watt	N/A	FO30/835/XP/SS/ECO
30	F30T8/841/ES/ECO	N/A	F32T8/XL/SP41/WM/ECO	N/A	N/A	F32T8/ADV841/EW/LL/ALTO 30 Watt	N/A	FO30/841/XP/SS/ECO
32	F32T8/730/ECO	F32T8/730K	F32T8/SP30/ECO	F32T8/730/ECO	F32T8/730	F32T8/TL730/ALTO	F32T8/730	FO32/730/XP/ECO
32	F32T8/735/ECO	F32T8/735K	F32T8/SP35/ECO	F32T8/735/ECO	F32T8/735	F32T8/TL735/ALTO	F32T8/735	FO32/735/XP/ECO
32	F32T8/741/ECO	F32T8/741K	F32T8/SP41/ECO	F32T8/741/ECO	F32T8/741	F32T8/TL741/ALTO	F32T8/741	FO32/741/XP/ECO
32	F32T8/830/ECO	F32T8/830K	F32T8/SPX30/ECO	F32T8/830/ECO	F32T8/830	F32T8/TL830/ALTO	F32T8/830	FO32/830/XP/ECO
32	F32T8/835/ECO	F32T8/835K	F32T8/SPX35/ECO	F32T8/835/ECO	F32T8/835	F32T8/TL835/ALTO	F32T8/835	FO32/835/XP/ECO
32	F32T8/841/ECO	F32T8/841K	F32T8/SPX41/ECO	F32T8/841/ECO	F32T8/841	F32T8/TL841/ALTO	F32T8/841	FO32/841/XP/ECO
32	F32T8/830/HL/ECO	N/A	F32T8/XL/SPX30/HL/ECO	N/A	F32T8/830HL	F32T8/ADV830/ALTO	N/A	FO32/830/XPS/ECO
32	F32T8/835/HL/ECO	N/A	F32T8/XL/SPX35/HL/ECO	N/A	F32T8/835HL	F32T8/ADV835/ALTO	F32T8/HL/835	FO32/835/XPS/ECO
32	F32T8/841/HL/ECO	N/A	F32T8/XL/SPX41/HL/ECO	N/A	F32T8/841HL	F32T8/ADV841/ALTO	F32T8/HL/841	FO32/841/XPS/ECO
<b>T8 Fluorescent U-Bent, 6" Spacing, Low Mercury</b>								
28	FB28T8/830/6/ES/ECO	N/A	N/A	N/A	N/A	N/A	N/A	N/A
28	FB28T8/835/6/ES/ECO	N/A	N/A	N/A	N/A	N/A	N/A	N/A
28	FB28T8/841/6/ES/ECO	N/A	N/A	N/A	N/A	N/A	N/A	N/A
32	FB32T8/730/6/ECO	N/A	F32T8/SP30/U/6	FB32/730/6/ECO	N/A	FB32T8/TL730/6/ALTO	FB32T8/730/6	FBO32/730/6/ECO
32	FB32T8/735/6/ECO	F32T8/735K/U6	F32T8/SP35/U/6	FB32/735/6/ECO	FB32T8/735/6	FB32T8/TL735/6/ALTO	FB32T8/735/6	FBO32/735/6/ECO
32	FB32T8/741/6/ECO	F32T8/741K/U6	F32T8/SP41/U/6	FB32/741/6/ECO	FB32T8/741/6	FB32T8/TL741/6/ALTO	FB32T8/741/6	FBO32/741/6/ECO
32	FB32T8/830/6/ECO	N/A	F32T8/SPX30/U/6	FB32/830/6/ECO	FB32T8/830/6	FB32T8/TL830/6/ALTO	FB32T8/830/6	FBO32/830/6/ECO
32	FB32T8/835/6/ECO	F32T8/835K/U6	F32T8/SPX35/U/6	FB32/835/6/ECO	FB32T8/835/6	FB32T8/TL835/6/ALTO	FB32T8/835/6	FBO32/835/6/ECO
32	FB32T8/841/6/ECO	F32T8/841K/U6	F32T8/SPX41/U/6	FB32/841/6/ECO	FB32T8/841/6	FB32T8/TL841/6/ALTO	FB32T8/841/6	FBO32/841/6/ECO



Lighting for life.™

**HOWARD**  
LIGHTING PRODUCTS

Surround yourself with **Howard Lighting**. We did.



Nestled within the 504 acre Howard Technology Park, our new corporate headquarters are surrounded and filled with our superior lighting products. From the round back floods featured to the left and compact fluorescents throughout the approximately 62,000 square feet of office space to the high bays illuminating the roughly 77,000 square foot Howard Computers and Howard Medical manufacturing facilities, we are your total lighting resource.

# HOWARD

LIGHTING PRODUCTS



*A Division of Howard Industries, Inc.*

580 Eastview Drive • Laurel, MS 39443  
P.O. Box 1590 • Laurel, MS 39441

800.956.3456 *general* • 601.422.1652 *fax*  
601.422.0033 *direct*

[www.HowardLightingProducts.com](http://www.HowardLightingProducts.com)